

# DOMINATOR® HIRO™

SUITABLE FOR USE ON HIGH ROLLING SHEET DOORS



## POWERHOUSE PERFORMANCE FOR DEMANDING APPLICATIONS

Slim but powerful - To suit demanding applications. Not only is it the most powerful rolling sheet door operator in our range, it is also smartphone compatible.

The GDO-12 Hiro™ is not only the most powerful opener in our range but it is also suitable for low side room installation. It paves the way in control and connectivity delivering smart phone control in residential and commercial applications (as an optional upgrade). If you need to operate a very large roller door or a wind-locked door, or have a site with low side room requirement, GDO-12 Hiro™ is the ideal choice.

### WHAT'S INCLUDED:



Opener with LED  
Courtesy Light



Wireless wall button and Two  
TrioCode™ 128 Remote Controls



Adaptors for JANUS sheet doors



Safety Beams

### AT A GLANCE:

#### SECURE & RELIABLE TRANSMITTERS

The TrioCode™ 128 remote control ensures secure and reliable home access. It transmits on three frequencies to defeat radio interference and uses a 128-bit encryption protocol (with trillions upon trillions of random codes\*) for the ultimate in security.



\*340,282,366,920,938,463,463,374,607,431,768,211,456 codes

#### KEY FEATURES

- 1400N Short-term peak force
- Soft Start / Soft Close
- Slim fit design
- LED Courtesy Light
- Intelligent Safety System
- Smart phone compatible

#### INTELLIGENT SAFETY SYSTEM (ISS)

If contact is made with an obstruction while moving, the opener either stops or reverses the door to reduce the risk of injury or property damage.

#### SOFT START / SOFT CLOSE

The Soft Start / Soft Close feature ramps speed up and down at the start and end of each cycle, therefore reducing stress on the door and opener.

## TECHNICAL SPECIFICATIONS

<b>Power</b>	Input Voltage	120 V
	Motor Type	24V d.c. Permanent Magnet
	Current (max)	2A
<b>Installation<sup>1</sup></b>	Door Size	300 ft <sup>2</sup>
	Door Size (wind-lock)	236 ft <sup>2</sup>
<b>Transmitter System</b>	Receiver/Transmitter Frequency	Multi-frequency UHF FM (434.37, 433.47 & 433.92MHz)
	Coding System	TrioCode <sup>™</sup> 128, code hopping
	Code Combinations	3.4x10 <sup>38</sup> code combinations
	Transmitter Capacity (x 4-button registers)	64
<b>Features</b>	Courtesy Light	LED
	Safety Beam Compatibility	2-wire Safety Beams
	Installation	Suits most sheet doors*
<b>Optional Accessories</b>	Battery backup	Optional
	Smart Phone Control Kit	Optional
<b>Warranty<sup>2</sup></b>	2 year/10,000 cycles on parts 1 year on accessories	

\*Suits most rolling sheet doors. Not suitable for rolling steel doors

### OPTIONAL ACCESSORIES



**Auto-Ki Smart Phone Control Kit**  
Monitor and operate your garage door on your smart phone from anywhere.\*

\*Subject to cellular and WiFi connection. Phone not included.



**Battery Backup**  
Operation during power outage.



**Keypad**  
Weather resistance, secure access without a transmitter or keys is great for school kids and active families.

### SAFETY & SECURITY FEATURES

- Soft Start/Soft Close
- Intelligent Safety System
- Door Profiling
- TrioCode<sup>™</sup> 128
- Network ready

### POWER & MOUNTING SYSTEMS

- DC Motor
- Battery Backup

### OPERATING MODES & FEATURES

- LED Courtesy Lights
- Auto Close
- Service Indicator
- Vacation Mode
- AUX Auxiliary Output

\* See our website for our icon glossary explanations.

1. Please note, suitable for use on dead axle doors only and windy conditions may trigger the obstruction feature on the opener.
2. Please see full warranty terms and conditions on our website. This brochure is not evidence of our warranty. Our warranty is in addition to any consumer guarantees that may apply under American Law.

Member of:

Automatic Technology America  
3626 North Hall Street, Suite 610, Dallas, TX 75219, United States of America

SMART  
SIMPLE  
SECURE