

## Product Overview

This product is designed for use with EMX loop detectors in a carwash environment. The proper location is between the rails where product cannot be struck or driven over.

Note: Walking on the unit may cause the wires to flex causing detection. Steel arch supports or steel toe shoes may also cause the detector to output a detect signal. Tires or other objects striking the SP-24 may cause it to detect and or cause damage to the pad.

## Cautions and Warnings

### IMPORTANT:

If the equipment is used in a manner not specified in this manual, the protection provided by the equipment may be impaired.

This product is an accessory or part of a system. Always read and follow the manufacturer's instructions for the equipment before connecting this product. Comply with all applicable codes and safety regulations. Failure to do so may result in damage, injury or death.

## Specifications

Size:	23.5 in x 23.5 in x 1.0 in
Material:	Black Polypropylene
Connections:	50 Foot 2 conductor lead wire
Detection Range:	~ 30 inches
Accessories:	SP-24 Guard (24 in x 3 in x 0.5 in)



## Ordering Information

SP-24      Surface Mounted Loop Pad

EMX Industries Inc.  
4564 Johnston Parkway  
Cleveland, Ohio 44128  
United States of America  
[www.emxinc.com](http://www.emxinc.com)

Technical Support:  
(216) 834-0761  
[technical@emxinc.com](mailto:technical@emxinc.com)

Sales:  
(216) 518-9888  
Fax (216) 518-9884  
[salesupport@emxinc.com](mailto:salesupport@emxinc.com)

